TALLIN 1200 0902

astro

SKU 1116004



PRODUCT SPECIFICATION

GENERAL

FINISH: Polished Chrome CABLE LENGTH: MAIN MATERIAL: Metal - Aluminium **GROSS WEIGHT:** H: 40mm W: 1200mm D: 80mm

DIMENSIONS: CLASS: CE (Class II) INSTALLATION ORIENTATION: Wall Mount IP RATING: IP44

Not Applicable **CUT OUT HOLE: BATHROOM ZONE:** Zone 2, 3 **RECESS DEPTH:** Not Applicable VOLTAGE: Mains 230V

FIRE RATING: Not Applicable PRODUCT F MARK: Suitable for mounting on flammable materials

LAMP

LIGHT SOURCE: T5 High Output MACADAM ELIPSE: Not Applicable MAXIMUM WATTAGE: 54W UGR: Not Applicable MAXIMUM LAMP LENGTH: **BEAM ANGLE:**

Not Applicable Not Applicable LAMP INCLUDED? No TILT ADJUSTMENT ANGLE: Not Applicable **LUMINOUS FLUX:** 1543.5 (lm) **ROTATION ADJUSTMENT ANGLE:** Not Applicable

COLOUR TEMP: AVERAGE LIFESPAN: Lamp Dependent 12,000 (Hrs) CRI: Lamp Dependent L70: Not Applicable

R9: -16.2

ELECTRICAL

SWITCHED: SUPPLY FREQUENCY: 50/60 (Hz) No DIMMABLE: No DRIVER/BALLAST VOLTAGE: 220-240 (V) DIMMING METHOD: Not Applicable DRIVER AVERAGE LIFESPAN: Not Applicable **DRIVER OUTPUT CURRENT:** Not Applicable EFFICACY: 31.68 (lm/W)

DRIVER OUTPUT VOLTAGE: DRIVER/BALLAST INCLUDED? Not Applicable Yes (Integral)

ADDITIONAL INFORMATION





This product is not suitable for use with a PIR motion detector.



BOX QUANTITY X4

Not Applicable

3.75 (kg)

